Project:	Type:	Quantity:	
J= =) F =	-, -, -,	

The Calzada is a contemporary low energy area light. Decoratively crafted design adds essential safety and security. Superior lasting LED technology delivers reliable low maintenance lighting service. Extremely rugged construction provides a lifetime of service.

Engineered specifically for today's LED technology the Calzada's design provides critical thermal transfer. Excellent heat removal ensures high performance and reliability of its LED light source. Other features include anti-wicking power lead and service upgrade capability.

The Calzada is available in multiple finishes and accessories. Suitable for use in wet locations.

Specification

Light Source Lighting Class LED*

LED Rated Life 50,000 hours average **

Input 12 Vac

Power Consumption 3 Watts Maximum

Standard LED Color 2700K +/- 175 CCT Typical

CRI 80 Typical

Lens Cover 3/16 inch Clear Acrylic

Cable Lead 3ft 18-2 AWG Direct Burial Rated

Standard Mounting ABS Cap and PVC Post
Operating Temperature -31F to 122F (-35C to 50C)

Maintenance Field serviceable Cable and LED module

Thermal Management Fixture is utilized as heat sink

Ingress Protection IP66

Control Dimmable with phase dimming transformer

Certification




^{*} IES LM-80 Standard ensures led light source will provide lumen maintenance and color performance.

Remote Low Voltage Transformer Required

Dimensions inches [mm]



Mounting Options (Not to Scale)



^{*} Specify Separately

Ordering Guide

Example: CZ-BR-27-18-N Calzada, Brass, 2700K, 18 inch post, Natural Finish, Pedestal Mount

CZ Prefix Material LED Color Finish Mounting BR - Brass 27 - 2700K N - Natural PV - ABS Cap PVC Post (Standard) PC - Metal Cap * CU - Copper 30 - 3000K BK - Black BS - Cast Brass Spike 40 - 4000K WT - White PM - Pedestal Mount BN - Brown GN - Green * Specify Separately MP - Silver NK - Nickel PT - Patina



C - Custom

^{**} LED life is defined as the time to 70% lumen maintenance (L70)