

Flow 90

Product Description

Flow 90 Recessed downlights utilise warm dimming technology. As the downlight dims the colour temperature warms up from 3000K evenly through to 1900K, creating an atmosphere that is relaxed and intimate, perfect for hospitality applications.

The COB Chip and reflector are deeply housed to reduce glare, while maintaining a compact size in this simple neat fitting.

Available in both fixed and adjustable versions.

Fixed version available in IP44 or IP20 Version

Product Details

Application	General Illumination	
Trim Colours	White	
Materials	Aluminium body	
LED	Sharp COB LED	

Technical Data

recillical Data	
Input Power	240V
Power Consumption	16W
CRI	>92
Lumen Maintenance	70% at 33 000 hrs
Dimming	Leading Edge Triac
	Trailing Edge Triac
Cut Out	90mm
Beam Angle	30°/60°
Tilt (on adjustable model)	25°
Warranty	5 year limited warranty

Luminous Flux

Current	Power	Luminous Flux	ССТ	CRI
25mA	3W	46lm	1970K	>92
50mA	4W	80lm	2022K	>92
100mA	6W	210lm	2508K	>92
200mA	10W	451lm	2843K	>92
300mA	15W	669lm	2962K	>92
350mA	16W	728lm	2982K	>92

Order Information

Specify fitting options as per example below to order.

Example: FL9 - F - 3 - NB

FITTING FL9	Housing	Colour 3 -	Beam
FL9 Flow 90	F Fixed A Adjustable	3 White	NB Narrow Beam (35°) WB
FL9-IP IP44	F Fixed		Wide Beam (60°)





